

June 2014



# PRODUCT CERTIFICATION

## PRODUCT : POLYESTERSTRAP WG

|             |          |          |          |           |
|-------------|----------|----------|----------|-----------|
| Article:    | WG40/250 | WG40/350 | WG40/500 | WG40/1100 |
| Length (m): | 250      | 350      | 500      | 1100      |
| Core Ø mm:  | 60       | 60       | 60       | 76        |
| Threads:    | 15       | 15       | 15       | 15        |

Minimum breaking strength: 375 kilopond;

Material: 85 % twisted polyester yarn 15 % hotmelt glue  
Width: 13 mm Tolerance for roll length: +/- 2%

## CERTIFICATION OF THE POLYESTER YARN

|                    |               |
|--------------------|---------------|
| Dtex:              | 3300          |
| Tenacity per dtex: | 8,1 cN +/- 2% |
| Elongation:        | 13.5 +/- 3%   |

## CALCULATION OF THE BREAKING STRENGTH

Threads x Dtex x Tenacity per dtex = 400 kg

Dimitrios Moustos  
Executive Director

### Lampero Grup SRL

Independentei 3  
087015 Bolintin Deal  
Romania

Tel.:+40 246708200

Fax:+40 346819169

Internet

[www.lampero.ro](http://www.lampero.ro)